




- •1.5" to 6.0" manual reset
- •1.5" to 3.5" auto reset
- Internally switched 12V or 24V switches from Pull to Hold automatically.

•Simple 2-wire installation

•No control module or relays



Use crimp type connectors & heat shrink tube on both 12V and 24V Solenoids. WIRE SIZE RECOMMENDATION TABLE

Maximum lead length (in feet)					
	<u>14 GA</u>	<u>12 GA</u>	<u>10 GA</u>	<u>8 GA</u>	<u>6 GA</u>
12 V DC	9.5	15	24	38	60
24 V DC	38	60	96	150	240

IMPROPER GROUNDING CAN CAUSE DAMAGE AND VOID WARRANTY ~ ONE YEAR PARTS WARRANTY ON SOLENOID ~

and the second s

Included in each kit:

- Toggle switch & military style toggle switch guard
- Auto reset breaker and rubber cover for breaker
- 2 clamps
- One year parts warranty

Extra mounting parts can be provided if required.

AMERICAN DISTRIBUTION CENTER LOCATED IN HASTINGS NEBRASKA

Manufactured by: Headwind Solutions 4331-41 Street Camrose, Alberta, Canada T4V 3V8



www.headwindsolutions.ca sales@headwindsolutions.ca Office: 1.780.672.2775 Toll Free: 1.844.304.7277 (PASS)

MADE IN NORTH AMERICA

TWO YEAR PARTS WARRANTY

©2023 Headwind Solutions. All Rights Reserved • 780-672-2775 • Toll Free: 1-844-304-7277 • www.headwindsolutions.ca • V1.01/27 Feb. 2023