

SHOCKER POSITIVE AIR SHUTOFF SYSTEM

MG Series

WHY CHOOSE OUR VALVE?

- · Simplicity at its Finest
- Only One Moving Part
- No external moving parts
- Patent Pending
- 5 amp 12 volt or 2.5 amp 24 volt draw
- No Plastic Gears or Electric Motors
- Solid Billet Aluminum Components for Superior Strength and Durability
- Corrosion resistant coatings and stainless steel fasteners
- Over 80,000 Continuous Test Cycles
- Solid state weather resistant Electronic Controller
- Plug & Play Harness
- Stringent Quality Control each unit is hand tested



AUTO RESET SYSTEM

- RPM controlled overspeed activation
- Auto Reset/Manual Override
- · Activation source
 - CAN J1939 message
 - Engine pulse (mag sensor)
- In hose style, 4" and up

OPTIONS

- 12V and 24V activation
- · Insta-bead
- · Multiple speed sensors





- Standard Touchpad
 - automatically resets valve after 17 seconds.



- Fuel Hauler Option
- press twice to reset valve.
- B621-14 & B622-14 Compliant Touchpad

AMERICAN DISTRIBUTION CENTER LOCATED IN HASTINGS NEBRASKA

Manufactured by:

Headwind Solutions 4331-41 Street Camrose, Alberta, Canada T4V 3V8



www.headwindsolutions.ca

sales@headwindsolutions.ca Office: 1.780.672.2775 Toll Free: 1.844.304.7277 (PASS)

MADE IN NORTH AMERICA

TWO YEAR PARTS WARRANTY