# SHOCKER POSITIVE AIR SHUTOFF SYSTEM

XK-Body Internally Switched Kits

# **REGULAR CONFIGURATION**

POSITIME AIR SHUTOFF SYSTEM



### **INLINE CONFIGURATION**



• 1.5" to 4.0" auto reset

+0

+0

-(

12 V DC

24 V DC

BATTERY

- Internally switched 12V or 24V switches from PULL
  - to HOLD automatically.
- Valve function unaffected by orientation

INTERNALLY SWITCHED SOLENOID WIRING DIAGRAM

12 VOLT

Use crimp type connectors & heat shrink tube on both 12V and 24V Solenoids.

WIRE SIZE RECOMMENDATION TABLE

Maximum lead length (in feet)

60

IMPROPER GROUNDING CAN CAUSE DAMAGE AND VOID WARRANTY ~ ONE YEAR PARTS WARRANTY ON SOLENOID ~

12 GA | 10 GA |

96

150

4 GA

38

- Switch up Valve closed / Switch down - Valve open
- No cable maintenance
- Fast 2 wire installation
- No control modules or relay's

# **Each kit includes:**

- Valve
- Toggle switch & cover
- Auto reset breaker & cover
- 2 hoses
- 4 clamps
- Wiring kit (15 feet) +terminal ends
- One Year All Inclusive Parts Warranty

# AMERICAN DISTRIBUTION CENTER LOCATED IN HASTINGS NEBRASKA

Manufactured by: Headwind Solutions 4331- 41 Street Camrose, Alberta, Canada T4V 3V8



www.headwindsolutions.ca sales@headwindsolutions.ca Office: 1.780.672.2775 Toll Free: 1.844.304.7277 (PASS) Fax: 1.780.672.6411

SOLENOID

6 GA

60

240

### MADE IN NORTH AMERICA

## ONE YEAR PARTS WARRANTY

©2020 Headwind Solutions. All Rights Reserved • 780-672-2775 • Fax: 780-672-6411 • Toll Free: 1-844-304-7277 • www.headwindsolutions.ca • V1.01/19 June 2022